

# Android

## Weight and measurement

Dimensions (width x height x depth)	35,5x80x7,5 cm
Weight (net weight and no supports)	14 kg

## Specifications

Voltage range	110-240V AC
Nominal frequency	50/60 Hz
Consumption	110 W - 220W
Working Temperature	0°C ~ 40°C, 10% ~ 90% RH, non-condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH, non-condensing
Scanner	Bar codes and QR
RFID	13.56MHz ISO4443A MIFARE, NFC

## Processor and communication

CPU Android	RK3568A Quad Core 2 GHz 4GB DDR3 SDRAM, 32GB eMMC
Touch screen	LED 21,5" FHD Display (16:9 diagonal), 280 nits
N° píxels	1920 x 1080
Touch panel	Capacitive multi-touch type
OS Supported	Android 11
I/O	4 x USB 2.0, 1 x USB 3.0 Type A, 1 x HDMI, 1 x LAN
Connection	Ethernet
Wireless	Wi-Fi 2.4G, Bluetooth 4.0G

## Print specifications

Ticket Printer	Thermal printing
Speed	170mm/seg (max)
DPI Resolution	576 DPI
Paper width	80mm
Paper roll diameter	Max Ø 83mm
Auto cutter	✓
Emulation	ESC/POS Command compatible

# Windows

## Weight and measurement

Dimensions (width x height x depth)	35,5x80x7,5 cm
Weight (net weight and no supports)	15 kg

## Specifications

Voltage range	110-240V AC
Nominal frequency	50/60 Hz
Consumption	110 W - 220W
Working Temperature	0°C ~ 40°C, 10% ~ 90% RH, non-condensing
Storage Temperature	-20°C ~ 60°C, 10% ~ 90% RH, non-condensing
Scanner	Bar codes and QR
RFID	13.56MHz ISO4443A MIFARE, NFC

## Processor and communication

CPU Windows	Intel Core i5 3337U, 3M Cache, 1.80 GHz, 8GB, 128GB SSD
Touch screen	LED 21,5" TFT-LCD, 280 nits
N° píxels	1920 x 1080
Touch panel	Capacitive multi-touch type
OS Supported	Windows 10
I/O	4 x USB 2.0, 2 x USB 3.0 Type A, 1 x HDMI, 1 x VGA, 2 x RS232, 1 x LAN
Connection	Ethernet
Wireless	Wi-Fi 2.4G, Bluetooth 4.0G

## Print specifications

Ticket Printer	Thermal printing
Speed	170mm/seg (max)
DPI Resolution	576 DPI
Paper width	80mm
Paper roll diameter	Max Ø 83mm
Auto cutter	✓
Emulation	ESC/POS Command compatible



## Model I

Credit card payment kiosk  
and information point

